



## Clear Lamination Film for General Use Fenix PX-850-L00

|                            |  |                  |                                |                |                    |
|----------------------------|--|------------------|--------------------------------|----------------|--------------------|
| <b>Product Description</b> | #100 Clear Polypropylene, Economy  |                  |                                |                |                    |
| <b>Construction</b>        | Film   | Adhesive         | Overall Thickness              | Film Thickness | Adhesive Thickness |
|                            | Biaxially Oriented Polypropylene   | Emulsion Acrylic | 0.95 mil                       | 0.70 mil ± 3%  | 0.25 mil ± 3%      |
| <b>Physical Properties</b> | Note: The following technical information and data should be considered representative or typical only.                            |                  |                                |                |                    |
|                            | Tensile Strength   |                  | 14 lbs/in                      |                |                    |
|                            | Elongation at Break  |                  | 150%                           |                |                    |
|                            | 180° Peel Adhesion   |                  | 12 oz/in                       |                |                    |
| <b>Special Features</b>    | <ul style="list-style-type: none"> <li>• Resistant to UV light</li> <li>• Excellent resistance to chemical and abrasion</li> </ul> |                  |                                |                |                    |
| <b>Temperature Range</b>   | <b>Application Temperature</b>   |                  | <b>Operating Temperature</b>   |                |                    |
|                            | 32° F to 150° F  |                  | 0° F to 200° F (nominal range) |                |                    |
| <b>Web Width</b>           | 60.5"  |                  |                                |                |                    |
| <b>Standard Length</b>     | 5,000'/10,000  |                  |                                |                |                    |
| <b>Government Specs</b>    | CFR 177.1520 & CFR 175.105   |                  |                                |                |                    |

v.20151207